

This page has the codes needed to connect and disconnect Scanfob® 2002 as a keyboard using Bluetooth. This page is divided into four quadrants and is designed to be folded once horizontally and once vertically to isolate the codes for scanning. The codes are located in the middle of each quadrant. Print both this sheet and the [second page](#) and follow the [instructions on the website](#) about folding.

Step 1. Scan the code in this quadrant to set the Scanfob® 2002 to HID keyboard mode. It will warble when the code is recognized:



Step 2. On your iPhone, bring up Settings / General / Bluetooth to prepare for pairing.

Step 3. Hold down the small button on the Scanfob® for 5 seconds to start pairing. When you do, it will emit a continuous beeping tone and the iPhone will show a message that includes a 4-digit PIN code.

Step 4. Using the second printed sheet, scan the four numeric barcodes in the order presented on the pairing message and then scan the “END” barcode. During pairing, the Scanfob will beep continuously and warble each time a number is recognized.

Step 5. After scanning the END code, the Scanfob 2002 will beep and the LED slowly flash blue indicating a good Bluetooth connection.

Step 6. If you have an iPhone, iPad or iPod, scan the code below:



When you are done scanning, you will want to disconnect the Scanfob and turn its radio off – but do so in a manner where you don’t have to go through the pairing procedure again! To do so, scan the code below.

If you have turned the Scanfob off temporarily and want to turn it back on without going through pairing again, use the code below.



